

Super Duty F-Series Tow Hook Billet Grille # 4090

1. Remove toe hook on each side. Some trucks you must loosen bumper bolts one side at a time to get to eye bolts. After removal of eye bolts retighten bumper bolts.
2. Mount brackets on back of grille, with tab to top. The L bracket will step down and back with long side back. Now use long bolts through long end of bracket, then set grille in bumper with bolt going down through toe hook holes. Some adjusting may be necessary to square up grille. Tighten with allen wrench going in through front.

Super Duty F-Series Tow Hook Billet Grille # 4090

1. Remove toe hook on each side. Some trucks you must loosen bumper bolts one side at a time to get to toe hook bolts. After removal of eye bolts retighten bumper bolts.
2. Mount brackets on back of grille, with tab to top. The L bracket will step down and back with long side back. Now use long bolts through long end of bracket, then set grille in bumper with bolt going down through toe hook holes. Some adjusting may be necessary to square up grille. Tighten with allen wrench going in through front.

Super Duty F-Series Tow Hook Billet Grille # 4090

1. Remove toe hook on each side. Some trucks you must loosen bumper bolts one side at a time to get to toe hook bolts. After removal of eye bolts retighten bumper bolts.
2. Mount brackets on back of grille, with tab to top. The L bracket will step down and back with long side back. Now use long bolts through long end of bracket, then set grille in bumper with bolt going down through toe hook holes. Some adjusting may be necessary to square up grille. Tighten with allen wrench going in through front.